
STEEL FITTING WITH NUT SEAL HOLE

OBJECTIVE

This product's main purpose is to connect a steel pipe or any other compatible material to an element or equipment by welding at one end and by threading at the other end.

APPLICATIONS

The most common applications are plumbing in general, heating, solar energy, natural gas and LPG installations, thermal installations, cold installations, diesel, and gasoline networks in general.

DIMENSIONS AND TOLERANCES

According to UNE 60719. Suitable for PN25 Bar.

MATERIALS

- Carbon steel ST 52 for the coupling.
- Brass CW617N (UNE-EN 12165), CW614N (UNE-EN 12164) or CB754S (UNE-EN 1982) for the nut

AVAILABLE DIMENSIONS

Please see our catalogue on our web site www.pareta.com



ASSEMBLY INSTRUCTIONS

Make sure that there is no type of leak in any of the connection parts of this accessory with the pipe and the connected element or equipment.

Verify that all the connections are free of tensions, both to traction, torsion, bending, compression, or shear. In case of installations that may suffer vibrations, make sure to incorporate the necessary elements so that these vibrations are not transmitted to the pipeline or to this connection fitting. If the installation can suffer contractions and expansions, incorporate the necessary elements to it so that they are compensated.

Choose the optimal size of fitting, according to the sizing of the installation pipe and its flow.

Always use the types of welding materials indicated by the standards required for each application.

In case of any doubt or special application, please contact our technical department.